

GO BEYOND NORMAL LIMITS

...with the Ritron Liberty™ Repeater!

5 WATT
NOW AVAILABLE



*Lib·er·ty (libərti:) n. 1). freedom
2). an action going beyond
normal limits.*

**Another Ritron revolution in on-site two-way radio communications
.... Announcing the ultra-small, self-contained Liberty Repeater.**

The Liberty Repeater is the perfect wireless solution for on-site communication needs. Industrial plants, stores, schools, golf courses, and other "tough-to-cover" applications no longer need to suffer from the limitations common to all brands of portable two-way radios. When the antenna location is optimized for the area of operation, the Liberty Repeater provides rock solid communication from one radio to another, virtually eliminating shadowing, fading, and dead spots.



The Liberty Repeater is the perfect wireless solution for:

**Golf Courses • Schools • Retail Stores • Nursing Homes • Shopping Malls
Manufacturing Plants • Warehouses • Amusement Parks • Hospitals • Special Events**



Rugged and compact, the Liberty repeater is a completely integrated wireless solution. The Liberty repeater is specifically designed "from the-ground-up" to be just that...an integrated, full duplex, PC programmable on-site repeater. Big in performance and features, yet small in size, the Liberty measures only 2.125"H x 8.0"W x 5.75"D. It's all-metal, powder coated, extruded aluminum housing provides durability and protection for the electronics and duplexer, while built-in mounting flanges make the Liberty easy to install.



Optional Remote Speaker for PTT & Local Audio

NEW!



Ritron has a full complement of wireless products for your two-way radio communications.

VHF/UHF Portable Radios -Communicate with personnel instantly at a push-of-the-button. Rugged and lightweight with built-in weather scan (VHF models only), and Interference Elimination features.



OutPost® Callbox -Puts communication right where it's needed. Wireless technology installs quickly and easily *without costly trenching, monthly charges or air-time fees*. Provides long-range (miles, not feet) communication between radio-equipped personnel and the OutPost callbox. Increases utilization of existing systems by allowing system-access from even the most remote locations. Improves security and safety of the facility *without* additional personnel.



TeleSwitch® Wireless Switch Control

Allows long-range, wireless, remote-control of up to 2 relays (switches), using touch-tone signaling. Use either a touch-tone equipped portable, mobile or base station to remotely control pumps, fans, machinery, gates, lights, strobes, sirens...



VHF/UHF Wireless Voice Alarm Reporter -Ideal for monitoring doors or limited access areas. Connect to any contact closure or switch and this battery-operated radio transmitter monitors critical areas on a 24/7 basis. Transmits a "custom" voice alert message to all radio-equipped personnel. *It's like being in two places at once!*



VHF/UHF Two-way Base Station/Wireless Intercom

Great 24/7 2-way radio monitoring. Ideal for service desk, office administration, and security. Stationary desktop or wall mount radio is compatible with virtually any VHF or UHF radio. Includes built-in weather scan (VHF models only) and Interference Eliminator features. Operates on 110 VAC or 12 VDC, so no batteries are required.

Always ready...always there...always on!



Call 800-USA-1-USA

The right Wireless Solutions for your communication needs.

Go Beyond Normal Limits...™

RITRON®
WIRELESS SOLUTIONS

P.O. Box 1998 • Carmel, Indiana 46082-1998 • 317-846-1201 • Fax: 317-846-4978

email: ritron@ritron.com • www.ritron.com

©2002-2006 Ritron, Inc. All rights reserved. Ritron, Patriot, Jobcom, OutPost, GateGuard, Quiet Call, Teleswitch and Quick Assist are registered trademarks of Ritron, Inc. Quick Talk, Liberty, RadioNexus, and LoudMouth are trademarks of Ritron, Inc. P/N14610026 rev. B 05/06

We've been designing and manufacturing wireless communications products for over 25 years. And the Liberty repeater is yet another Ritron breakthrough in on-site, wireless RF communication technology.

- Frequency Range: 450-470 MHz – 400-430MHz coming soon!
- Narrow or Wide Bandwidth Versions Available
- Frequency Stability: + 1.5 ppm (-30° to +50° C)
- Integrated Full Duplex Radio and Duplexer w/ "N" Connector
- Power On and Transmit Indicator LED's
- Includes 110VAC to 12VDC Wall-Mount Power Supply
- RJ-12 Jack For Remote Speaker Microphone
- CTCSS or DCS Signaling (1 CTCSS or 2 DCS codes)
- Synthesized & PC Programmable
(tuning required and Windows based Ritron PC Software)
- Compact size 2.125" H X 8.0" W X 5.75" D & Lightweight: 3.5 lbs
- Built-In Mounting Flanges
- Proudly designed, manufactured, and serviced in the USA

If you need to "go beyond normal limits" with your portable radios, call Ritron. We have wireless solutions! **Call 800-USA-1-USA.**

GENERAL	WIDE BAND 25 kHz	NARROW BAND 12.5 kHz
Models: 2 Watt 5 Watt	RLR-460-W RLR-465-W	RLR-460 RLR-465-N
FCC ID:	AIERIT15-460	AIERIT15-460
IC:	1084A-RLR-460	1084A-RLR-460
FCC Parts:	90, 95A	90, 95A
Dimensions:	2.125"H x 8.0" W x 5.75" D	2.125"H x 8.0" W x 5.75" D
Weight:	3.5 lbs.	3.5 lbs.
Emission Designators:	14K8F3E	11K1F3E
Operating Frequency Range:	450-470 MHz	450-470 MHz
Frequency Separation:	TX/RX: 5.0 MHz	TX/RX: 5.0 MHz
RF Channels:	(1) TX/RX Channel	(1) TX/RX Channel
Synthesized Steps:	12.5 kHz	12.5 kHz
Tone/Code Signalling:	1 QC (Quiet Call) or 2 DQC (Digital Quiet Call) modes	1 QC (Quiet Call) or 2 DQC (Digital Quiet Call) modes
Power Requirements: (2 Watt) (5 Watt)	12 VDC nominal @ 1A 12 VDC nominal @ 1.5A 1/8 Watt into 8 Ohms	12 VDC nominal @ 1A 12 VDC nominal @ 1.5A 1/8 Watt into 8 Ohms
Local Audio Output:	0 to 8 seconds, programmable	0 to 8 seconds, programmable
Hang-Time Timer:	0 to 8 seconds, programmable	0 to 8 seconds, programmable
Squelch Tail Eliminator Timer:	0 to 30 minutes, programmable	0 to 30 minutes, programmable
Time-out Timer:	"N" Type	"N" Type
RF Connector:	P-5 (2.1mm X 5.51mm X 9.5 mm)	P-5 (2.1 mm X 5.51mm X 9.5 mm)
DC Power Connector:	50 Ohms	50 Ohms
Antenna Impedance:	50 Ohms	50 Ohms
Test Speaker Microphone:	RJ-12	RJ-12
TRANSMITTER		
RF Output @ antenna port:	5/2 Watt	5/2 Watt
Frequency Stability:	+/- 1.5 PPM (-30° C to +50° C)	+/- 1.5 PPM (-30° C to +50° C)
Modulation:	Direct FM	Direct FM
Deviation:	0 to +/- 5 kHz, adjustable	0 to +/- 2.5 kHz, adjustable
Spurious & Harmonics:	< -20 dBm	< -20 dBm
Audio Response:	10 to 2500 Hz (+/- 3 dB)	10 to 2500 Hz (+/- 3 dB)
FM Hum & Noise:	-50 dB	-45 dB
Duty Cycle:	100/25%	100/25%
RECEIVER		
Receiving System:	Fixed Tuned, Dual Conversion Superhetrodyne	Fixed Tuned, Dual Conversion Superhetrodyne
IF System:	43.65 MHz/450 kHz	43.65 MHz/450 kHz
Local Oscillator:	Low Side Injection	Low Side Injection
Sensitivity (12 dB SINAD):	0.28 uV through duplexer	0.28 uV through duplexer
Selectivity (EIA):	-75 dB @ +/- 25 kHz	-65 dB @ +/- 12.5 kHz
Spurious Rejection (EIA):	-75 dB	-75 dB
Image Rejection (EIA):	-80 dB	-80 dB
Intermodulation Rejection (EIA):	-70 dB	-70 dB
Frequency Stability:	+/- 1.5 PPM (-30° C to +50° C)	+/- 1.5 PPM (-30° C to +50° C)
Noise Squelch Sensitivity:	8-18 dB SINAD, adjustable - factory set to open @ 12 dB	8-18 dB SINAD, adjustable - factory set to open @ 12 dB
Audio Frequency:	10 Hz to 3 kHz	10 Hz to 3 kHz

Your Ritron Dealer:

BUY TWO WAY RADIOS

**528 S. Cherry Road
Rock Hill, SC 29732
1-800-584-1445**

www.buytwowayradios.com